



**LEAD LINED ACCESS DOOR
BA-KATR-LL
For Drywall Ceilings**

DATE _____



228 Park Ave S # 76520
New York NY 10003-1502
United States
www.BestAccessDoors.com
info@bestaccessdoors.com
Tel.: 1-800-483-0823
Fax: 1-888-828-6021

PROJECT DATA					
Project Name:					
Architect:					
Contractor:					
Agent/Customer Name:					
Tagging Instructions:					
Special Instructions:					

CONSTRUCTION:

1. Frame shall be 16 gage steel and doors all be 18 gage steel.
2. Door shall be recessed 1 1/2" to accommodate double thickness of wall board.
3. Hinge shall be exposed, continuous piano hinge.
4. Locks shall be flush and screwdriver operated with 1 1/2" cam and lock studs, or shall be key operated cylinder lock with automatic dust shutter. Furnished with plastic grommet for studs only to protect hole made in wall board.
5. Finish shall be prime coat of rust inhibitive electrostatic powder, baked white enamel.
6. Sheet metal meets National Council of Radiation Protection #49.
7. Varying thicknesses of lead available. Custom door sizes also available.

PROJECT SCHEDULE					
Qty.	H	W	No. of Latches	Finish	Remarks

STANDARD SIZES

DOOR SIZE H X W (IN.)	WALL/CEILING OPENING (IN.)	NUMBER OF LATCHES	SHIP WT. (LBS.)
12 x 12	10 1/2 x 10 1/2	1	6.7
18 x 18	16 1/2 x 16 1/2	2	11.6
24 x 24	22 1/2 x 22 1/2	2	18.1
30 x 22	28 1/2 x 20 1/2	2	19.5

