



Quality Access Doors- FAST!

# SUBMITTAL/TECHNICAL DATA SHEET

## DESCRIPTION

A premium flush mount supply vent cover for a 6"x12" duct. Complete with diffuser flaps to control your air flow, this cover fits into the drywall opening of 4"x13" and has a vented/slotted area of 5"x11".

## APPLICATION

- Designed for 1/2" and 5/8" thick drywall.
- Suitable for both wall and ceiling installation.
- Screws on to the face of your drywall.
- Once finished seaming over the flange, the product is ready to be primed and painted to your wall colour.
- The inserts comes primed white and ready for your paint colour.


## FEATURES

- Magnetic removable triple fibre reinforced cement board grill.
- 24 gauge galvanized satin coat steel frame complete with a beaded edge and adjustable diffuser.
- 4 rare earth magnets (0.250" diameter x 0.060" thick).
- Easy installation, primed and ready to paint.
- Rectangular straight vent slots.
- Fire Rated, non-flammable.
- Impact Resistant.
- Moisture and Water Resistant, Mold Resistant.
- Eco-Friendly Manufacturing and Non-Hazardous.

## SPECIFICATIONS

- Over 20.8 square inches (134.2 square centimeters) of open area.
- Slot Size: 0.26" x 5" (6.6mm x 127mm).
- 16 rectangular straight vertical slots.
- Overall dimensions are 15.5" x 9.5" x 0.5" (393.7mm x 241.3mm x 12mm).
- Product weight is 1.9 pounds (0.86 kilograms)


For a complete list of options visit [www.BestAccessDoors.ca](http://www.BestAccessDoors.ca)



SKU: **BAC-IG-MAG-S6X12**  
**WALL AND CEILING SUPPLY VENT**  
 REMOVABLE AND MAGNETIC


## DIMENSIONS AND APPEARANCE

>> [CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<](#)



### MATERIAL INFORMATION:

Raw Material: cement, fibres, quartz sand, non-hazardous fillers.  
 Density: 1.0 < D ≤ 1.2 g/cm<sup>3</sup>  
 Asbestos Content: 100% asbestos-free  
 Fire resistance: non-combustible  
 Water Absorption: ≤40%  
 Resistant Bending Strength: ≤10.5 MPa dry  
 Moisture Movement: 0.25 %  
 Freeze Thaw: No distortion after 25 repeated cycles of freezing and thawing .



## PROJECT DATA

Custom Sizes Available - Fast!

Scan or Click



PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :				
TAGGING INSTRUCTIONS :	SUBMITTAL APPROVAL : (signature or stamp)			

To view Pricing and Additional Product Info.



TELEPHONE:  
1-800-483-0823  
FAX:  
1-888-828-6021



385 WILSON STREET EAST,  
SUITE 302  
ANCASTER, ON, L9G 2C1  
CANADA



WEBSITE:  
[www.BestAccessDoors.ca](http://www.BestAccessDoors.ca)  
E-MAIL:  
[info@bestaccessdoors.ca](mailto:info@bestaccessdoors.ca)